

Pipeline Processing Equipment Catalogue: Pipeline Maintenance Equipment

TORQUE MACHINE

Topline HY-Air Pneumatic Pump is the most trusted industrial Torque and Tension system.

The HY-Air Hydraulic Pump features a 10 meter or 30 feet long remote control air, a 4-tool adapter, and a psi / bar FS 1.0% indicator. It is semi-automatic (-A) and the device has a guaranteed gauge with a license according to EU-Directive 94/9EG (Atex 100a) class.

Options:

Calibrated gauge with certificate / Two gallon reservoir

Features:

Protective Caging

Light Weight

3-Stage

4-Tool Adapter

Remote Control Air – 5m Length



HY-AIR HYDRAULIC PUMP

SPECIFICATIONS:

Model: HYTORC HY-Air Hydraulic Pump

Air Consumption:

400 – 1000 kPa / 60L/s

(4 – 10 bar)

55 – 150 psi / 3800 cu.in/sec.

Dimensions:

A = 20.4" (520mm)

B = 10.9" (275mm)

C = 15.5" (395mm)

Weight:

46.3 lbs (21 kg) – without oil

Oil Flow:

Max Oil flow: 770 cu.in/min (12.5 l/min)

Up to 1000 psi (bis 70 bar)

Middle Pressure Oil flow: 135 cu.in/min (2.2 l/min)

Up to 4200 psi (bis 300 bar)

High Pressure Oil flow: 66 cu.in/min (1.0 l/min)

Up to 10,000 psi (bis 700 bar)

www.toplinelimited.com

.....your one-stop shop in pipeline & process engineering.....