

Pipeline Processing Equipment Catalogue: Process Equipment

DOOSAN AIR COMPRESSOR

Topline Pipeline DOOSAN Air Compressors are rugged and suitable for Onshore and Offshore operations.

Doosan Portable Power offers a skid-mounted, open-frame, high pressure unit with reliable design features. The unit is designed for stationary applications such as oil and gas drilling, and comes mounted on a heavy-duty skid, without on-board fuel tanks and without an enclosure. The fuel tanks can be added as an option on EXPORT units only. All service drains are centrally located allowing maintenance to be performed quickly and easily.

High dependability and long live.



DOOSAN AIR COMPRESSOR

SPECIFICATIONS:

Make: DOOSAN Infracore

Model: XHP900SCAT (Free Air Delivery)

Rated Delivery: 425 Litres /Sec. (900 cfm)

Rated Pressure: 350 Psi

Power: 360 Amp

Engine Model: CAT3406BTA (Caterpillar – Diesel)

Full Load Speed: 1800 RPM
No Load Speed: 1200 RPM
Electrical System: 24 Volts

Weight: 5,800 Kg

Dimension:

Length: 5.70m Width: 2.25m Height: 2.58m

Fluid Capacity:

Compressor Lubricant: Initial (dry) Fill: 208 Litres

Service Refill: 167 Litres

Fluel Tank (Clean Diesel): 680 Litres